

## Cabinet Lock KK-CL-50

- Compact and easy to install, suitable for drawer, cabinet, locker, and etc.
- Adjustable fail-safe (power to lock) or fail-secure (power to open), according to user's need.
- Door position state output to detect door location (open or close door).
- Dual-mounting directions available for user to choose.
- Adjustable DC12V/DC24V dual-voltage design.
- Maximum of 100 kg holding force.



### SPECIFICATION

|                     |  |
|---------------------|--|
| Model Available     | : KK-CL-50 (Cabinet Lock)                |
| Power Supply        | : DC 12V/24V ± 15%                       |
| Current Consumption | : 150 MA@12VDC ± 15% ; 75 MA@24VDC ± 15% |
| Signal Output       | : Door position detection (COM/NO/NC)    |
| Application         | : Mailbox, Drawer, Locker                |
| Door Leaf Width     | : > 25cm                                 |
| Holding Force       | : 100Kg (220 lbs)                        |
| Lock Type           | : Fail-safe or fail-secure (adjustable)  |
| Mounting            | : Front or side                          |
| Operation Temp.     | : 0° - 80°C                              |
| Operation Humidity  | : 85% Rh max.                            |
| Weight              | : 335g (G.W.)                            |

\* Design & dimension subject to change without prior notice, please contact us for further information.