

Turnstile Product Information



**Tripod Slim
with Soap Dispenser**



**Tripod Slim
Turnstile**



**Tripod Standard
Turnstile**



**Double Tripod Slim
Turnstile**



**Double Tripod
Turnstile**



**Full Height
Turnstile**

Model No.	KK-MSL-01	KK-101	KK-100	KK-103	KK-102	KK-121a/121b
Dimension (LxWxH)	420 x 330 x 1080 mm		1200 x 280 x 1000 mm	500 x 420 x 980 mm	1600 x 260 x 1010 mm	1630 x 1500 x 2310 mm
Materials	SUS304 Brushed Stainless Steel					
Passenger Width	≤550mm		≤600mm			≤650mm
Voltage	AC220±10V 50Hz					-
Passing Speed	20 Passenger/min					20-35 person/min
Working Temp.	-20°C to 60°C		-15°C to 60°C			-25°C to 70°C
Input Port	+12V Level or >100ms DC 12V Pulse signal					-
Com. Interface	RS485					
Input Signal	Dry Contact					
Arm	Stainless Steel					
Driving Motor	-	-	-	DC Brush Motor		
Method of Position	-	-	-	Motor Driving		
IP Rating	IP54					IP65
Warranty*	1 Year					

* Please consult with us

** Specification may change without prior notice

Turnstile Product Information



Swing Gate
Turnstile 01



Swing Gate
Turnstile 02



U Swing Gate
Turnstile



High-End Speed Swing
Gate Turnstile



Flap Barrier
Turnstile

Model No.	KK-111B/112B	KK-111A/112A	KK-SW-01	KK - 141	KK-131A/132A
Dimension (LxWxH)	1400 x 200 x 1000 mm	1600 x 210 x 1000 mm	Ø168 x 990 mm	1600 x 140 x 1000 mm	1600 x 280 x 980 mm
Materials	SUS304 Brushed Stainless Steel				
Passenger Width	≤1050mm	≤1050mm	600mm, max 1200mm	-	≤550mm
Voltage	AC110V/AC220V±10% 50-60Hz		AC220V, 50Hz	AC220V±10% 50Hz	AC110V/AC220V±10% 50-60Hz
Passing Speed	30 person/min	30~50 person/min	-	35~40 person/min	30-45 person/min
Working Temp.	-20°C to 70°C	-25°C to 70°C	-	-25°C to 70°C	-20°C to 60°C
Input Port	-	-	-	-	-
Com. Interface	RS485, TCP/IP		-	Level/Pulse/RS485/RS232	RS485
Input Signal			-	-	Dry Contact
Arm	Acrylic/Stainless Steel	Plexiglass/Stainless Steel	Acrylic/ Glass	Acrylic (Tempered Glass for Optional)	12mm PC Arm
Driving Motor	DC Brush Motor		-	-	-
Method of Position	Use the encoder to make sure position		-	Motor + Clutch + Encoder	-
IP Rating	IP54		IP24	IP42	IP22
Warranty*	1 Year				

* Please consult with us

** Specification may change without prior notice